


 <i>Products for tomorrow...</i>	Europe: +49 / 7731 8399 0	Email: info@meder.com	Item No.:
	USA: +1 / 508 295 0771	Email: salesusa@meder.com	9183100014
	Asia: +852 / 2955 1682	Email: salesasia@meder.com	Item:
			MK18-C-100W

Dimensions mm[inch]


tolerances acc. to DIN ISO 2768-m
Toleranzen gem. DIN ISO 2768-m




Cable
single wires UYw/T 0,141 mm², black
Einzellitzen UYw/T 0,14 mm², schwarz

Terminals/Connector
ends tinned
Enden verzinkt

Schematic



Isometric
Scale 1:2
Maßstab 1:2



Marking
according to EN60062/factory code
gem. EN60062/Fertigungsstätte



Magnetic properties	Conditions	Min	Typ	Max	Unit
Pull-In	at 20°C	40		61	AT
Test equipment		KMS-13			

Special Product Data	Conditions	Min	Typ	Max	Unit
Contact - No.			87		
Contact - form			A - NO		
Contact rating	Any DC combination of V & A not to exceed their individual max.'s			10	W
Switching voltage	DC or Peak AC			200	V
Carry current	DC or Peak AC			0,5	A
Switching current	DC or Peak AC			0,5	A
Sensor-resistance	measured with 40% overdrive			250	mOhm
Housing material		PBT glass fibre reinforced			
Case colour		black			
Sealing compound		Polyurethan			

Environmental data	Conditions	Min	Typ	Max	Unit
Shock	1/2 sine wave duration 11ms			50	g
Vibration	from 10 - 2000 Hz			20	g
Operating temperature	cable not moved	-30		80	°C
Operating temperature	cable moved	-5		80	°C
Storage temperature		-30		80	°C
Reach / RoHS conformity		yes			

General data	Conditions	Min	Typ	Max	Unit
Mounting advice		over 5m cable, a resistor is recommended.			